



podkładka nierdzewna okrągła
din 125, ISO 7089 PN 82006.

UWAGI:

- A2
- A4



d	do gwintu	d2	h	A2	A4
1.7	M1.6	4.0	0.3	●	●
1.8	M1.7	4.5	0.3	●	●
2.2	M2	5.0	0.3	●	●
2.5	M2.3	6.0	0.5	●	●
2.7	M2.5	6.0	0.5	●	●
2.8	M2.6	7.0	0.5	●	●
3.2	M3	7.0	0.5	●	●
3.7	M3.5	8.0	0.5	●	●
4.3	M4	9.0	0.8	●	●
5.3	M5	10.0	1.0	●	●
6.4	M6	12.0	1.6	●	●
7.4	M7	14.0	1.6	●	●
8.4	M8	16.0	1.6	●	●
10.5	M10	20.0	2.0	●	●
13.0	M12	24.0	2.5	●	●
15.0	M14	28.0	2.5	●	●
17.0	M16	30.0	3.0	●	●
19.0	M18	34.0	3.0	●	●
21.0	M20	37.0	3.0	●	●
23.0	M22	39.0	3.0	●	●
25.0	M24	44.0	4.0	●	●
28.0	M27	50.0	4.0	●	●
31.0	M30	56.0	4.0	●	●
34.0	M33	60.0	5.0	●	●
37.0	M36	66.0	5.0	●	●
40.0	M39	72.0	6.0	●	●
43.0	M42	78.0	7.0	●	●
46.0	M45	85.0	7.0	●	●
50.0	M48	92.0	8.0	●	●