



podkładka nierdzewna sprężysta

DIN: 127, PN-82008.

UWAGI:

- A2
- A4



d	do gwintu	d1	d2	h min	s	b	A2/A4
2.0	M2	2.1	4.4	1.0	0.5	0.9	● ●
2.3	M2.3	2.3	4.8	1.2	0.6	1.0	● ●
2.5	M2.5	2.6	5.1	1.2	0.6	1.0	● ●
2.6	M2.6	2.7	5.2	1.2	0.6	1.0	● ●
3.0	M3	3.1	6.2	1.6	0.8	1.3	● ●
3.5	M3.5	3.6	6.7	1.6	0.8	1.3	● ●
4	M4	4.1	7.6	1.8	0.9	1.5	● ●
5	M5	5.1	9.2	2.4	1.2	1.8	● ●
6	M6	6.1	11.8	3.2	1.6	2.5	● ●
8	M8	8.1	14.8	4.0	2.0	3.0	● ●
10	M10	10.2	18.1	4.4	2.2	3.5	● ●
12	M12	12.2	21.1	5.0	2.5	4.0	● ●
14	M14	14.2	24.1	6.0	3.0	4.5	● ●
16	M16	16.2	27.4	7.0	3.5	5.0	● ●
18	M18	18.2	29.4	7.0	3.5	5.0	● ●
20	M20	20.2	33.6	8.0	4.0	6.0	● ●
22	M22	22.5	35.9	8.0	4.0	6.0	● ●
24	M24	24.5	40.0	10.0	5.0	7.0	● ●
27	M27	27.5	43.0	10.0	5.0	7.0	● ●
30	M30	30.5	48.2	12.0	6.0	8.0	● ●
33	M33	33.5	55.2	12.0	6.0	10.0	● ●
36	M36	36.5	58.2	12.0	6.0	10.0	● ●
39	M39	39.5	61.2	12.0	6.0	10.0	● ●
42	M42	40.5	63.5	14.0	7.0	12.0	● ●
45	M45	42.5	68.2	14.0	7.0	12.0	● ●
48	M48	49.0	75.0	14.0	7.0	12.0	● ●