



podkładka nierdzewna sprężysta
DIN 128 A

UWAGI:

- A2
- A4



d	do gwintu	d1 min	d2 max	h min	h max	s	b	A2/A4
2.0	M2	2.1	4.4	0.70	0.90	0.5	0.9	● ●
2.3	M2.3	2.3	4.8	0.90	1.10	0.6	0.9	● ●
2.5	M2.5	2.6	5.1	0.90	1.10	0.6	1.0	● ●
2.6	M2.6	2.7	5.2	0.90	1.10	0.6	1.0	● ●
3.0	M3	3.1	6.2	1.10	1.30	0.7	1.3	● ●
3.5	M3.5	3.6	6.7	1.10	1.30	0.7	1.3	● ●
4.0	M4	4.1	7.6	1.20	1.40	0.8	1.5	● ●
5.0	M5	5.1	9.2	1.50	1.70	1.0	1.8	● ●
6.0	M6	6.1	11.8	2.00	2.20	1.3	2.5	● ●
8.0	M8	8.1	14.8	2.45	2.75	1.6	3.0	● ●
10.0	M10	10.2	18.1	2.85	3.15	1.8	3.5	● ●
12.0	M12	12.2	21.1	3.35	3.65	2.1	4.0	● ●
14.0	M14	14.2	24.1	3.90	4.30	2.4	4.5	● ●
16.0	M16	16.2	27.4	4.50	5.10	2.8	5.0	● ●
18.0	M18	18.2	29.4	4.50	5.10	2.8	5.0	● ●
20.0	M20	20.2	33.6	5.10	5.90	3.2	6.0	● ●
22.0	M22	22.5	35.9	5.10	5.90	3.2	6.0	● ●
24.0	M24	24.5	40.0	6.50	7.50	4.0	7.0	● ●
27.0	M27	27.5	43.0	6.50	7.50	4.0	7.0	● ●
30.0	M30	30.5	48.2	9.50	10.50	6.0	8.0	● ●
36.0	M36	36.5	58.2	10.30	10.50	6.0	10.0	● ●