


pierścień wewnętrzny INOX  
DIN 472

UWAGI:

- A2
- A4



D	d3	d5min	a max	b-	s	A2	D	d3	d5min	a max	b-	s	A2
8	8.7	1.0	3.2	1.5	0.80	●	52	56.2	2.5	7.0	5.2	2.0	●
9	9.8	1.0	3.3	1.7	1.00	●	55	59.2	2.5	7.2	5.4	2.0	●
10	10.8	1.2	3.3	1.8	1.00	●	58	62.2	2.5	7.4	5.8	2.0	●
11	11.8	1.2	3.3	1.8	1.00	●	60	64.2	2.5	7.4	5.8	2.0	●
12	13.0	1.5	3.3	1.8	1.00	●	62	66.2	3.0	7.8	6.3	2.5	●
13	14.1	1.7	3.4	2.0	1.00	●	65	69.2	3.0	7.8	6.3	2.5	●
14	15.1	1.7	3.5	2.1	1.00	●	68	72.2	3.0	8.1	6.6	2.5	●
15	16.2	1.7	3.6	2.2	1.00	●	70	74.5	3.0	8.1	6.6	2.5	●
16	17.3	1.7	3.7	2.2	1.00	●	72	76.5	3.0	8.4	7.0	2.5	●
17	18.3	1.7	3.8	2.3	1.00	●	75	79.5	3.0	8.4	7.0	2.5	●
18	19.5	2.0	3.9	2.4	1.00	●	80	85.5	3.0	8.6	7.4	2.5	●
19	20.5	2.0	3.9	2.5	1.20	●	85	90.5	3.5	8.7	7.8	3.00	●
20	21.5	2.0	4.0	2.6	1.20	●	90	95.5	3.5	8.8	8.2	3.00	●
21	22.5	2.0	4.2	2.8	1.20	●	95	100.5	3.5	9.4	8.6	3.00	●
22	23.5	2.0	4.3	2.9	1.20	●	100	105.5	3.5	9.6	9.0	3.00	●
23	24.6	2.0	4.4	3.0	1.20	●	105	112.0	3.5	9.9	9.3	4.00	●
24	25.9	2.0	4.4	3.0	1.20	●	110	117.0	3.5	10.1	9.6	4.00	●
25	26.9	2.0	4.4	3.0	1.20	●	120	127.0	3.5	11.0	10.2	4.00	●
26	27.9	2.0	4.5	3.1	1.20	●	130	137.0	4.0	11.6	10.7	4.00	●
27	28.9	2.0	4.6	3.1	1.20	●	140	147.0	4.0	12.0	11.2	4.00	●
28	30.1	2.0	4.7	3.2	1.50	●							
29	31.1	2.0	4.8	3.4	1.50	●							
30	32.1	2.0	5.0	3.5	1.50	●							
31	33.4	2.5	5.2	3.6	1.50	●							
32	34.4	2.5	5.2	3.6	1.50	●							
34	36.5	2.5	5.4	3.8	1.50	●							
35	37.8	2.5	5.6	3.9	1.50	●							
36	38.8	2.5	5.6	4.0	1.75	●							
37	39.8	2.5	5.8	4.2	1.75	●							
38	40.8	2.5	5.9	4.3	1.75	●							
39	42.2	2.5	6.0	4.4	1.75	●							
40	43.5	2.5	6.5	4.5	1.75	●							
41	44.5	2.5	6.7	4.7	1.75	●							
42	45.5	2.5	6.9	5.0	1.75	●							
45	48.5	2.5	6.9	5.1	2.0	●							
47	50.5	2.5	7.0	5.2	2.0	●							
48	51.5	2.5	7.2	5.4	2.0	●							
50	54.2	2.5	7.0	5.2	2.0	●							