



wkręty nierdzewne z łbem grzybkowym z gniazdem imbusowym
ISO 7380

UWAGI:

- A2
- A4



dk	5,7	7,6	9,5	10,5	14	17,5	21
k max	1,65	2,20	2,75	3,30	4,40	5,50	6,60
s	2	2,5	3	4	5	6	8
t	1,04	1,30	1,56	2,08	2,60	3,12	4,16
	2	2,5	3	4	5	6	8
Ø	M3	M4	M5	M6	M8	M10	M12
4	● ●	● ●					
5	● ●	● ●					
6	● ●	● ●	● ●				
8	● ●	● ●	● ●	● ●			
10	● ●	● ●	● ●	● ●	● ●		
12	● ●	● ●	● ●	● ●	● ●	● ●	
14	● ●	● ●	● ●	● ●	● ●	● ●	
16	● ●	● ●	● ●	● ●	● ●	● ●	
18	● ●	● ●	● ●	● ●	● ●	● ●	
20	● ●	● ●	● ●	● ●	● ●	● ●	
22	● ●	● ●	● ●	● ●	● ●	● ●	● ●
25	● ●	● ●	● ●	● ●	● ●	● ●	● ●
30	● ●	● ●	● ●	● ●	● ●	● ●	● ●
35	● ●	● ●	● ●	● ●	● ●	● ●	● ●
40	● ●	● ●	● ●	● ●	● ●	● ●	● ●
45		● ●	● ●	● ●	● ●	● ●	● ●
50		● ●	● ●	● ●	● ●	● ●	● ●
55			● ●	● ●	● ●	● ●	● ●
60			● ●	● ●	● ●	● ●	● ●
65				● ●	● ●	● ●	● ●
70				● ●	● ●	● ●	● ●
75				● ●	● ●	● ●	● ●
80				● ●	● ●	● ●	● ●